Hiraoka (Australia) Pty Ltd



ABN 74 108 919 615
2/37 Rimfire Drive Hallam Vic 3803 Australia
Tel. 03 8795 7322 Fax. 03 9703 2476
Email. info@hiraoka.com.au

HIRAOKA CLEARWEAVE

Technical Data

Hiraoka Clearweave is a clear reinforced PVC fabric. **Clearweave** is dimensionally stable, has excellent FR levels and is easier to handle than heavy clear unreinforced PVC materials.

This fabric is ideally suited for applications where high light transmission combine with a stable material is required. Applications include café blinds, tent and marquee walls, factory and office partitions and machine covers.

Base Fabric	Polyester reinforced mesh
Coating	PVC
Weight (g/m²)	610
Thickness (mm)	0.47
Tensile Strength (N/50mm)	330 x 325
Elongation (%)	19 x 28
Tear Strength (N)	210 x 200
Fungal Resistance	Treated
Antiwick	Yes
Fire Retardant	Yes (AS1530.2 & AS1530.3)
Cold Crack Resistance (°C)	-20
Roll Size (m)	2.04 x 30

The above results are typical averages taken from quality assurance testing. Product technical data are subject to change without notice. *for further details see separate warranty statement.

Last Update - 2015