



## ULTRAMAX

## Technical Data

ULTRAMAX is a PVC coated fabric for awning, tent and similar applications. It utilises a special spun yarn in the base cloth to give excellent flexibility and ease of handling. The fabric top surface has a special fluorine lacquer for added long term dirt resistance.

<b>Base Fabric</b>	<b>Polyester – woven spun yarn</b>
<b>Coating</b>	<b>PVC with Fluorine Lacquer top coat and Acrylic Lacquer underside</b>
<b>Weight (g/m<sup>2</sup>)</b>	<b>560</b>
<b>Thickness (mm)</b>	<b>0.47</b>
<b>Tensile Strength (N/50mm)</b>	<b>2600 x 2200</b>
<b>Elongation (%)</b>	<b>25 x 30</b>
<b>Tear Strength (N)</b>	<b>88 x 98</b>
<b>Fungal Resistance</b>	<b>Treated</b>
<b>Antiwick</b>	<b>Yes</b>
<b>Fire Retardant</b>	<b>Yes</b>
<b>UV Warranty*</b>	<b>7 year pro rata available</b>
<b>Roll Size (m)</b>	<b>2.03 or 1.03 x 50</b>
<b>Colour</b>	<b>Various</b>

The above results are typical averages taken from quality assurance testing. Product technical data are subject to change without notice. \*for further details see separate warranty statement.

Last Update - 2018